

CUSTOM OPTIONS AVAILABLE CONTACT MPD FOR SWEEP, DIMMER, PULSE EFFECTS

NOTES:

1. MATERIAL:

HOUSING: BLACK POLYPROPYLENE, UL FILE NO. E108370

FLAMMABILITY RATED: UL 94-HB

TEMPERATURE RANGE: -40°C TO +85°C WIRES: 24 AWG, BLACK FOR NEGATIVE,

BLACK WITH WHITE TRACE FOR POSITIVE

BUTTON OVERLAY: 0.010" THICK MYLAR, PCB: SWITCH AND POSITIVE AND NEGATIVE

CONTACTS FOR BATTERY

SCREWS: M1.6x6Mmm CRS/NI PLATED

2. ROHS 2 COMPLIANT

Tolerance	■ MPD Mem	ory Prote	ction 1	Devices, Inc
(Except as noted)	200 Broad Hollow Road, Farmingdale, New York 11735			
decimal			Scale	Drawn By B.S.
±.5 (.020)				Approved By T.B.
Fractional	Title			
± .8 (.030)	ENCLOSED CR2032 BATTERY HOLDER WITH ON/OFF SWITCH			
Angular	Date	Drawing Number		
± 3°	5/06/16	BQ2032-3		

AUTH DR. CK.

B.S.

T.B.

REVISION RECORD

Updated material note